

MODELS

KBD-CG-(40, 50, 60, 80)-S KBD-CG-(40, 50, 60, 80)-R KBD-CG-(40, 50, 60, 80)-D

> CASE HOLDS 36°F TO 40°F • FORCED AIR REFRIGERATION • TEMPERED TILT-OUT CURVED FRONT GLASS • TEMPERED SIDE GLASS AND REAR SLIDING DOORS LED LIGHTING IN CANOPY AND UNDER ALL SHELVES CASES CAN BE MULTIPLEXED









: CONTAINED	Model	0.A. Length (inches)	Volume FT ³		Ele	ctrical 115	Volts		NEMA	Weight lbs		Crate Size (inches)		
			Front	Comp	ressor	essor LIGHTS Fans		Total	115 V Plug	No	With	L″	W″	Н″
				H.P	F.L.A	HTRS	Pan	Amps		Crate	Crate			
	KBD-CG-40-S	40.4	13.28	3/8	8.4	1.3	3.3	13.0	5-15P	375	514	43.04	34.5	62.3
SELF	KBD-CG-50-S	52.2	17.50	1/2	9.6	1.5	3.3	14.4	5-20P	436	604	55.02	34.5	62.3
	KBD-CG-60-S	60	20.31	1/2	9.6	1.6	3.3	14.5	5-20P	478	666	63	34.5	62.3
	KBD-CG-80-S	77.5	26.56	1/2	9.6	2.7	3.3	15.6	5-20P	557	787	80.5	34.5	62.3

		0.A.	115		Weight lbs		
OTE	Model	Length (inches)	Volts Total Amps	B.T.U	No Crate	With Crate	
REMOTE	KBD-CG-40-R	40.4	0.82	2621	319	459	
	KBD-CG-50-R	52.2	1.06	3110	381	549	
	KBD-CG-60-R	60	1.10	3268	423	611	
	KBD-CG-80-R	77.5	2.20	3987	502	732	

0		0.A.	115	NEMA	Weight lbs		
NON-REFRIGERATED	Model	Length (inches)	Volts Total Amps	115 V Plug	No Crate	With Crate	
	KBD-CG-40-D	40.4	0.29	5-15P	319	459	
N-R	KBD-CG-50-D	52.6	0.33	5-15P	381	549	
NO	KBD-CG-60-D	60	0.41	5-15P	423	611	
	KBD-CG-80-D	77.5	0.46	5-15P	502	732	

STANDARD FEATURES

Silver colored PVC coated steel front panel

CFC free injected foam insulation

PVC coated steel gray interior

Black steel kick plate

Foamed polystyrene black end panels

Removable rear tempered glass sliding door

Anti-condensate system for front glass

Removable condensate evaporating pan for easy cleaning on self contained units

Height adjustable, tempered glass shelves can be tilted

Temperature and defrost regulated by a digital controller

Digital temperature display

Cord and plug on self-contained and dry units

Leveling feet

OPTIONAL FEATURES

Stainless steel exterior and / or interior Other colors available

Additional shelves

Joining kit

Partition or product dividers

Scale stand with 120 V receptacle

Condensate evaporating pan for remote cases

Casters-add 4-3/8" to height

Stainless steel legs are adjustable from 5-1/8" to 7-5/8"


WARRANTY

One year parts and labor with an additional four years on the compressor (part only)



3560 NW 56th St Fort Lauderdale, FL USA 33309 Tel: 786.600.4687 / Toll Free: 844.218.8477 / Fax: 786.661.4100

5659 Royalmount Ave. Montreal, QC, Canada H4P 2P9 Tel: 514.737.9701 / Toll Free: 888.275.4538 / Fax: 514.342.3854 Toll free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com



Levelling Feet



Casters

NOTE

These cases are engineered to operate in locations not exceeding 75°F and 55% R.H. These cases are designed to operate using R404a refrigerant. Alternate refrigerants available by special order. O.A. length includes (2) ends at 1-1/2" each. Ventilation grills at front and back cannot be blocked. B.T.U.'s are calculated at 14°F (evaporator) and 90°F (ambient). Remote cases are provided with an expansion valve and a liquid solenoid for pump down cycle On remote cases, if no floor drain is provided, a condensate evaporating pan must be ordered and 3.3 amps added to the amp load. Remote cases must be hard wired - no plugs.



Hydra - Kool is a registered trademark of MVP Group Corp. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE