

DATE:	
DEALER:	
ADDRESS:	
BUYING GROUP:	<input type="checkbox"/> NONE <input type="checkbox"/> NAFED <input type="checkbox"/> IFED <input type="checkbox"/> STRATA
REQUESTOR:	
PHONE #:	
EMAIL:	
JOB NAME:	
JOB LOCATION:	
DELIVERY TO ZIP:	<input type="checkbox"/> CUSTOMER ARRANGE FREIGHT
SALES REP:	
EMAIL:	

APPLICATION TYPE: INDOOR OUTDOOR
BOX TYPE: COOLER FREEZER COMBO

PROVIDE A SKETCH:

INSULATION THICKNESS: 4" (STD) 5-3/8"
FOAM-IN-PLACE FLOOR: YES NO FREEZER ONLY
INTERIOR FLOOR FINISH:
 SMOOTH ALUMINUM ALUMINUM DIAMOND TREADPLATE
 OTHER: _____

FLOOR TYPE:
 STANDARD (1,200 LBS PER SQ FT)
 HEAVY DUTY (1,500 LBS PER SQ FT) *TYPICAL FOR KEGS
 PALLET JACK (2,600 LBS PER SQ FT)
 OTHER: _____

SPECIAL BUILDING REQUIREMENTS:
 ANCHORING PROVISIONS
 SEISMIC CALCULATIONS (REQUIRES ANCHORING PROVISIONS)

PANEL FINISHES (STUCCO EMBOSSED):

INTERIOR WALL FINISH	<input type="checkbox"/> STANDARD	<input type="checkbox"/> WHITE
CEILING INTERIOR	<input type="checkbox"/> STANDARD	<input type="checkbox"/> WHITE
EXPOSED EXTERIOR	<input type="checkbox"/> STANDARD	<input type="checkbox"/> WHITE
UNEXPOSED EXTERIOR	<input type="checkbox"/> STANDARD	<input type="checkbox"/> WHITE
DOOR FINISH	<input type="checkbox"/> STANDARD	<input type="checkbox"/> WHITE
OTHER:	_____	

SWING DOORS:

30" X 78"
 34" X 78" (STD)
 36" X 78"
 42" X 78"
 48" X 78"
 OTHER: _____

SLIDING DOORS:

<input type="checkbox"/> 36" X 78"	<input type="checkbox"/> MANUAL	<input type="checkbox"/> ELECTRIC
<input type="checkbox"/> 42" X 78"	<input type="checkbox"/> MANUAL	<input type="checkbox"/> ELECTRIC
<input type="checkbox"/> 48" X 78"	<input type="checkbox"/> MANUAL	<input type="checkbox"/> ELECTRIC
<input type="checkbox"/> 60" X 78"	<input type="checkbox"/> MANUAL	<input type="checkbox"/> ELECTRIC
<input type="checkbox"/> 72" X 78"	<input type="checkbox"/> MANUAL	<input type="checkbox"/> ELECTRIC

DOOR ACCESSORIES:

** STANDARD DOORS ARE EQUIPPED WITH BRUSHED CHROMED HANDLE WITH KEYLOCK, 36"H INT/EXT DIAMOND TREAD KICKPLATES, LIGHT SWITCH/THERMOMETER, VAPOR PROOF LED LIGHT, DOOR CLOSER, (2) CAM LIFT HINGES, ELECTRICAL CONDUIT, AND SAFETY NIGHT LIGHT.

STRIP CURTAIN 3RD CAM LIFT HINGE
 14" x 14" VIEW PORT 14" x 24" VIEW PORT

DISPLAY GLASS DOORS:

GLASS DOOR WIDTH 24" 26" 28" 30"
GLASS DOOR HEIGHT 67" 75" 79"
GLASS DOOR QUANTITY _____
HINGE DIRECTION LEFT RIGHT
SHELVING SIZE 24" DEEP 27" DEEP 36" DEEP
SHELVING TYPE FLAT SHELVING GRAVITY FEED
NO. OF SHELVING TIERS 5 6 7
FINISH SILVER BLACK
IF DOOR BY OTHERS, SPECIFY REQUIRED FRAMED OPENING: _____

BOX ACCESSORIES:

INTERIOR RAMP EXTERIOR RAMP METAL COVE BASE (CALIFORNIA)
 CLOSURE PANEL TRIM STRIPS LED LIGHTS NON-SKID STRIPS
 MASS INSULATION & VISQUEEN (FLOORLESS FREEZERS)
 SLOPING MATERIAL (MEMBRANE INCLUDED) MEMBRANE ONLY
 RAIN GUTTER (OVER DOOR)

REFRIGERATION: INDOOR OUTDOOR COMPRESSOR STAND
 REMOTE PRE-ASSEMBLED SELF-CONTAINED

VOLTAGE: 208/230/1 208/230/3 460/3

COOLER HOLDING TEMP: _____ °F **FREEZER HOLDING TEMP:** _____ °F
 FREEZER OPENING INTO A COOLER BEER IN COOLER

** STANDARD REFRIGERATION SYSTEMS ARE ENGINEERED FOR HOLDING TEMPERATURE ONLY AND 2 DOOR OPENINGS PER HOUR. HEAVY PRODUCT LOAD WITH HIGHER ENTERING TEMPRATURES IS NOT FACTORED INTO REFRIGERATION SIZING OR PULL-DOWN TARGETS. FOR SPECIAL CONDITIONS/REQUIREMENTS, PLEASE SPECIFY.

COMMENTS: